

Safety data sheet

Page: 1/16

BASF 3D Printing safety data sheet. This is a translation of the country-specific safety data sheet into a language other than that required by law. This document does not replace the safety data sheet provided according to Regulation (EC) No 1907/2006.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Ultrafuse ® 316L metal filament

- **1.2.** Relevant identified uses of the substance or mixture and uses advised against Recommended use: 3D Printing, for industrial use only
- 1.3. Details of the supplier of the safety data sheet

Company:
BASF 3D Printing Solutions B.V.
Eerste Bokslootweg 17
7821 AT Emmen, Netherlands

Contact address: BASF SE 67056 Ludwigshafen GERMANY

Telephone: +49 621 60-0

E-mail address: global.info@basf.com

1.4. Emergency telephone number

International emergency number: Telephone: +49 180 2273-112

SECTION 2: Hazards Identification

2.1. Classification of the substance or mixture

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

For the classification of the mixture the following methods have been applied: extrapolation on the concentration levels of the hazardous substances, on basis of test results and after evaluation of experts. The methodologies used are mentioned at the respective test results.

2.2. Label elements

Globally Harmonized System, EU (GHS)

The product does not require a hazard warning label in accordance with GHS criteria. The dangerous ingredients are fixed in a polymer matrix.

2.3. Other hazards

According to Regulation (EC) No 1272/2008 [CLP]

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture. Upon mechanical treatment like e.g. cutting, grinding and/or polishing the product can release hazardous substances. Upon thermal and/or chemical treatment the product can release hazardous substances.

SECTION 3: Composition/Information on Ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Chemical nature

polymer blend based on: Alloy, metal powder encapsulated, in a polymer matrix

<u>Hazardous ingredients (GHS)</u> according to Regulation (EC) No. 1272/2008

Iron

Content (W/W): >= 50 % - <= 75 % Flam. Sol. 1 CAS Number: 7439-89-6 Self-heat. 1 EC-Number: 231-096-4 H228, H251 REACH registration number: 01-

2119462838-24

nickel powder [particle diameter < 1mm]

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Content (W/W): >= 7 % - < 25 % Skin Sens. 1
CAS Number: 7440-02-0 Carc. 2
EC-Number: 231-111-4 STOT RE 1
REACH registration number: 012119438727-29 H317, H351, H372, H412

Chromium

Content (W/W): >= 7 % - < 25 % CAS Number: 7440-47-3 EC-Number: 231-157-5

REACH registration number: 01-

2119485652-31

Substance with EU occupational exposure limit

Molybdenum

Content (W/W): >= 0 % - < 10 % CAS Number: 7439-98-7 EC-Number: 231-107-2 REACH registration number: 01-2119472304-43

For the classifications not written out in full in this section, including the hazard classes and the hazard statements, the full text is listed in section 16.

SECTION 4: First-Aid Measures

4.1. Description of first aid measures

Remove contaminated clothing.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. If symptoms persist, seek medical advice.

On skin contact:

Wash thoroughly with soap and water Burns caused by molten material require hospital treatment. If irritation develops, seek medical attention.

On contact with eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. If irritation develops, seek medical attention.

On ingestion:

Keep patient calm, remove to fresh air. Immediate medical attention required.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms: (Further) symptoms and / or effects are not known so far

Hazards: No hazard is expected under intended use and appropriate handling.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

4.3. Indication of any immediate medical attention and special treatment needed

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

SECTION 5: Fire-Fighting Measures

5.1. Extinguishing media

Suitable extinguishing media: water spray, foam, dry powder

5.2. Special hazards arising from the substance or mixture

Endangering substances: carbon oxides

Advice: The substances/groups of substances mentioned can be released in case of fire.

5.3. Advice for fire-fighters

Special protective equipment:

Wear a self-contained breathing apparatus.

Further information:

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

SECTION 6: Accidental Release Measures

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Avoid the formation and build-up of dust - danger of dust explosion. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

6.1. Personal precautions, protective equipment and emergency procedures

No special precautions necessary.

6.2. Environmental precautions

Discharge into the environment must be avoided.

6.3. Methods and material for containment and cleaning up

For small amounts: Sweep/shovel up.

For large amounts: Sweep/shovel up. Vacuum up spilled product.

Reclaim for processing if possible. Ensure adequate ventilation. Avoid raising dust.

6.4. Reference to other sections

Information regarding exposure controls/personal protection and disposal considerations can be found in section 8 and 13.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Avoid inhalation of dusts/mists/vapours. Ensure adequate ventilation. Provide suitable exhaust ventilation at the drying process and in the area surrounding the melt outlet of processing machines.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Avoid the formation and deposition of dust.

Protection against fire and explosion:

The product is not an oxidizer, not self-combustible and not explosive. Avoid dust formation. Dust in sufficient concentration can result in an explosive mixture in air. Handle to minimize dusting and eliminate open flame and other sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Avoid deposition of dust.

Storage stability:

Protect against moisture.

The packed product is not damaged by low temperatures or by frost.

Protect from temperatures above: 165 °C

Changes in the properties of the product may occur if substance/product is stored above indicated temperature for extended periods of time.

7.3. Specific end use(s)

For the relevant identified use(s) listed in Section 1 the advice mentioned in this section 7 is to be observed.

SECTION 8: Exposure Controls/Personal Protection

8.1. Control parameters

Components with occupational exposure limits

7439-89-6: Iron

7439-98-7: Molybdenum 7440-47-3: Chromium

TWA value 2 mg/m3 (OEL (EU))

indicative

7440-02-0: nickel powder [particle diameter < 1mm]

Components with PNEC

7439-89-6: Iron

A PNEC could not be derived as no studies have been performed. The product is a naturally occuring substance, whose molecular structure is not supposed to have harmful effects.

7440-02-0: nickel

freshwater: 0.0036 mg/l freshwater: 0.0071 mg/l marine water: 0.0086 mg/l

STP: 0.33 mg/l

sediment (marine water): 109 mg/kg sediment (freshwater): 109 mg/kg

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

oral (secondary poisoning): 5.0 mg/kg

soil: 29.9 mg/kg

7439-96-5: Manganese

freshwater: 0.034 mg/l marine water: 0.0034 mg/l sediment (freshwater): 3.3 mg/kg sediment (marine water): 0.34 mg/kg

soil: 3.4 mg/kg STP: 100 mg/l

intermittent release: 0.028 mg/l

7440-47-3: Chromium

sediment (freshwater): 205.7 mg/kg

freshwater: 0.0065 mg/l

soil: 21.1 mg/kg

oral (secondary poisoning):

No PNEC oral derived, as accumulation in organisms is not to be expected.

Components with DNEL

7439-89-6: Iron

worker: Long-term exposure - local effects, Inhalation: 3 mg/m3 consumer: Long-term exposure- systemic effects, oral: 0.71 mg/kg consumer: Long-term exposure - local effects, Inhalation: 1.5 mg/m3

7440-02-0: nickel

worker: Long-term exposure - systemic and local effects, Inhalation: 0.05 mg/m3

worker: Short-term exposure - local effects, Inhalation: 11.9 mg/m3 worker: Long-term exposure - local effects, dermal: 0.035 mg/cm2 consumer: Short-term exposure - systemic effects, oral: 0.012 mg/kg consumer: Short-term exposure - local effects, Inhalation: 0.8 mg/m3 consumer: Long-term exposure - systemic and local effects, Inhalation:

0.00006 mg/m3

consumer: Long-term exposure- systemic effects, oral: 0.02 mg/kg

7439-96-5: Manganese

worker: Long-term exposure- systemic effects, Inhalation: 0.2 mg/m3 worker: Long-term exposure- systemic effects, dermal: 0.00414 mg/kg consumer: Long-term exposure- systemic effects, Inhalation: 0.041 mg/m3 consumer: Long-term exposure- systemic effects, dermal: 0.0021 mg/kg

7440-47-3: Chromium

worker: Long-term exposure - local effects, Inhalation: 0.5 mg/m3 consumer: Long-term exposure - local effects, Inhalation: 0.027 mg/m3

8.2. Exposure controls

Appropriate engineering controls

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

suppression system or an oxygen deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.

Personal protective equipment

Respiratory protection:

Breathing protection if breathable aerosols/dust are formed. Wear respiratory protection if ventilation is inadequate. Particle filter with medium efficiency for solid and liquid particles (e.g. EN 143 or 149, Type P2 or FFP2)

Hand protection:

Use additional heat protection gloves when handling hot molten masses (EN 407), e.g. of textile or leather.

Eve protection:

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures

Wear protective clothing to prevent contact during mechanical processing and/or hot melt conditions. Store work clothing separately. Hands and/or face should be washed before breaks and at the end of the shift.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Form: filament
Colour: grey
Odour: odourless

Odour threshold:

not applicable

pH value:

not applicable, substance/mixture is

non-soluble (in water)

Melting point: 165 °C

Boiling point:

not applicable

Flash point:

not applicable

Evaporation rate:

The product is a non-volatile solid.

Flammability: Not a flammable solid according to

UN transport regulations division 4.1

and GHS chapter 2.7.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Based on the structure or

composition there is no indication of

flammability

Lower explosion limit:

For solids not relevant for classification and labelling.

Upper explosion limit:

For solids not relevant for classification and labelling.

Ignition temperature:

not applicable

Vapour pressure:

not applicable

Density: 5.4 - 5.8 g/cm³

(20 °C)

Relative vapour density (air):

not applicable

Solubility in water: insoluble

Partitioning coefficient n-octanol/water (log Kow):

not applicable

Self ignition: not self-igniting

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

Prolonged thermal loading can result in products of degradation being

given off.

Viscosity, dynamic:

not applicable

Viscosity, kinematic:

not applicable, the product is a solid

Explosion hazard: not explosive

Product is not explosive, however a dust explosion could result from an

air / dust mixture.

Fire promoting properties: not fire-propagating

9.2. Other information

Self heating ability: It is not a substance capable of

spontaneous heating.

Radioactivity:

not radioactive for transport

purposes

Bulk density: 5 - 6 kg/m3 Hygroscopy: Non-hygroscopic

Solids content: > 90 %

SECTION 10: Stability and Reactivity

10.1. Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Corrosion to metals: No corrosive effect on metal.

Reactions with

water/air:

Reaction with: air

Flammable gases: no
Toxic gases: no
Corrosive gases: no
Smoke or fog: no
Peroxides: no

Reaction with: water
Flammable gases: no
Toxic gases: no
Corrosive gases: no
Smoke or fog: no
Peroxides: no

Formation of flammable gases:

Remarks:

Forms no flammable gases in the

presence of water.

10.2. Chemical stability

The product is stable if stored and handled as prescribed/indicated.

10.3. Possibility of hazardous reactions

No hazardous reactions when stored and handled according to instructions.

10.4. Conditions to avoid

Avoid dust formation. Avoid deposition of dust.

10.5. Incompatible materials

Substances to avoid: oxidizing agents

10.6. Hazardous decomposition products

Thermal decomposition products:

Prolonged thermal loading can result in products of degradation being given off.

SECTION 11: Toxicological Information

11.1. Information on toxicological effects

Acute toxicity

Assessment of acute toxicity:

Contact with molten product may cause thermal burns.

Information on: Iron

Assessment of acute toxicity:

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.

.

Irritation

Assessment of irritating effects: May cause mechanical irritation.

Experimental/calculated data:

Skin corrosion/irritation: May cause mechanical irritation.

Serious eye damage/irritation: May cause mechanical irritation.

Information on: Iron

Assessment of irritating effects:

Not irritating to the skin. Not irritating to the eyes. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Respiratory/Skin sensitization

Assessment of sensitization:

The chemical structure does not suggest a sensitizing effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: nickel Assessment of sensitization:

Sensitization after skin contact possible.

Germ cell mutagenicity

Assessment of mutagenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Iron

Assessment of mutagenicity:

Most of the results from the available studies show no evidence of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Information on: nickel

Assessment of carcinogenicity:

The results of various animal studies gave no indication of a carcinogenic effect. IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).

Reproductive toxicity

Assessment of reproduction toxicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Developmental toxicity

Assessment of teratogenicity:

The chemical structure does not suggest a specific alert for such an effect. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Specific target organ toxicity (single exposure)

Remarks: Based on available data, the classification criteria are not met.

Repeated dose toxicity and Specific target organ toxicity (repeated exposure)

Assessment of repeated dose toxicity:

Repeated exposure to the substance by dermal administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by inhalative administration leads to effects similar to those found after single exposure. Repeated exposure to the substance by oral administration leads to effects similar to those found after single exposure. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: nickel

Assessment of repeated dose toxicity:

The substance may cause damage to the lung after repeated inhalation.

Information on: Manganese

Assessment of repeated dose toxicity:

The substance may cause damage to the central nervous system after repeated inhalation of high doses

Aspiration hazard

No aspiration hazard expected.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Other relevant toxicity information

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

SECTION 12: Ecological Information

12.1. Toxicity

Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms. The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Information on: Chromium Assessment of aquatic toxicity:

There is a high probability that the product is not acutely harmful to aquatic organisms.

No toxic effects occur within the range of solubility.

12.2. Persistence and degradability

Assessment biodegradation and elimination (H2O):

The product is not very soluble in water and can thus be removed from water mechanically in suitable effluent treatment plants.

Information on: Chromium

Assessment biodegradation and elimination (H2O):

Not applicable for inorganic substances.

12.3. Bioaccumulative potential

Bioaccumulation potential:

The product has not been tested. Because of the product's consistency and low water solubility, bioavailability is improbable.

Information on: Chromium

Assessment bioaccumulation potential:

Does not significantly accumulate in organisms.

12.4. Mobility in soil

Assessment transport between environmental compartments: Adsorption in soil: Adsorption to solid soil phase is possible.

12.5. Results of PBT and vPvB assessment

According to Annex XIII of Regulation (EC) No.1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH): The product does not contain a substance

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

fulfilling the PBT (persistent/bioaccumulative/toxic) criteria or the vPvB (very persistent/very bioaccumulative) criteria.

12.6. Other adverse effects

The product does not contain substances that are listed in Regulation (EC) 1005/2009 on substances that deplete the ozone layer.

12.7. Additional information

The product contains:

The product contains the heavy metals listed in Section 3 and/or Section 8, which are fixed in a polymer matrix.

Add. remarks environm. fate & pathway:

The product has not been tested. The statements on environmental fate and pathway have been derived from the properties of the individual components.

Other ecotoxicological advice:

The product has been assessed on the basis of the components' available data. To some extent data gaps exist for individual components. According to our present knowledge and experience dangers which are not covered by the current labeling are not to be expected.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Dispose of in accordance with national, state and local regulations.

Contaminated packaging:

Dispose of in accordance with national, state and local regulations.

SECTION 14: Transport Information

Land transport

ADR

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

RID

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Inland waterway transport

ADN

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user:

Transport in inland waterway vessel

Not evaluated

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

user

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

UN number:
UN proper shipping name:
Transport hazard class(es):
Packing group:
Environmental hazards:
Special precautions for

Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

user

14.1. **UN** number

See corresponding entries for "UN number" for the respective regulations in the tables above.

14.2. UN proper shipping name

See corresponding entries for "UN proper shipping name" for the respective regulations in the tables above.

14.3. Transport hazard class(es)

See corresponding entries for "Transport hazard class(es)" for the respective regulations in the tables above.

14.4. Packing group

See corresponding entries for "Packing group" for the respective regulations in the tables above.

14.5. Environmental hazards

See corresponding entries for "Environmental hazards" for the respective regulations in the tables above.

14.6. Special precautions for user

See corresponding entries for "Special precautions for user" for the respective regulations in the tables above.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Regulation:
Shipment approved:
Pollution name:
Pollution category:
Ship Type:
Not evaluated
Not evaluated
Not evaluated
Not evaluated
Not evaluated

SECTION 15: Regulatory Information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Prohibitions, Restrictions and Authorizations

Annex XVII of Regulation (EC) No 1907/2006: Number on List: 27

Directive 2012/18/EU - Control of Major Accident Hazards involving dangerous substances (EU): Listed in above regulation: no

15.2. Chemical Safety Assessment

Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Date / Revised: 15.07.2021 Version: 5.0
Date previous version: 13.07.2020 Previous version: 4.0

Product: Ultrafuse ® 316L metal filament

(ID no. 11123987/SDS_GEN_EU/EN)

Date of print 30.08.2021

SECTION 16: Other Information

Full text of the classifications, including the hazard classes and the hazard statements, if mentioned

in section 2 or 3:

Flam. Sol. Flammable solids

Self-heat. Self-heating substances and mixtures

Skin Sens. Skin sensitization Carc. Carcinogenicity

STOT RE Specific target organ toxicity — repeated exposure Aquatic Chronic Hazardous to the aquatic environment - chronic

H228 Flammable solid.

H251 Self-heating: may catch fire.

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road. ADN = The European Agreement concerning the International Carriage of Dangerous Goods by Inland waterways. ATE = Acute Toxicity Estimates. CAO = Cargo Aircraft Only. CAS = Chemical Abstract Service. CLP = Classification, Labelling and Packaging of substances and mixtures. DIN = German national organization for standardization. DNEL = Derived No Effect Level. EC50 = Effective concentration median for 50% of the population. EC = European Community. EN = European Standards. IARC = International Agency for Research on Cancer. IATA = International Air Transport Association. IBC-Code = Intermediate Bulk Container code. IMDG = International Maritime Dangerous Goods Code. ISO = International Organization for Standardization. STEL = Short-Term Exposure Limit. LC50 = Lethal concentration median for 50% of the population. LD50 = Lethal dose median for 50% of the population. TLV = Threshold Limit Value. MARPOL = The International Convention for the Prevention of Pollution from Ships, NEN = Dutch Norm, NOEC = No Observed Effect Concentration, OEL = Occupational Exposure Limit. OECD = Organization for Economic Cooperation and Development. PBT = Persistent, Bioaccumulative and Toxic. PNEC = Predicted No Effect Level. PPM = Parts per million. RID = The European Agreement concerning the International Carriage of Dangerous Goods by Rail. TWA = Time Weight Average. UN-number = UN number at transport. vPvB = very Persistent and very Bioaccumulative.

The data contained in this safety data sheet are based on our current knowledge and experience and describe the product only with regard to safety requirements. This safety data sheet is neither a Certificate of Analysis (CoA) nor technical data sheet and shall not be mistaken for a specification agreement. Identified uses in this safety data sheet do neither represent an agreement on the corresponding contractual quality of the substance/mixture nor a contractually designated use. It is the responsibility of the recipient of the product to ensure any proprietary rights and existing laws and legislation are observed.